

Memory Module Specifications

KSM29SED8/32HC

32GB 2Rx8 4G x 72-Bit PC4-2933

CL21 260-Pin ECC SODIMM

DESCRIPTION

Kingston's KSM29SED8/32HC is a 4G x 72-bit (32GB) DDR4-2933 CL21 SDRAM (Synchronous DRAM) w/ parity, 2Rx8, ECC, memory module, based on eighteen 2G x 8-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR4-2933 timing of 21-21-21 at 1.2V. Each 260-pin SODIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

FEATURES

- Power Supply: VDD = 1.2V
- VDDQ = 1.2V
- VPP = 2.5V
- VDDSPD = 2.20V to 3.60V
- Functionality and operations comply with the DDR4 SDRAM datasheet
- 16 internal banks
- Bank Grouping is applied, and CAS to CAS latency (tCCD_L, tCCD_S) for the banks in the same or different bank group accesses are available
- Data transfer rates: PC4-2933, PC4-2666, PC4-2400, PC4-2133, PC4-1866, PC4-1600
- Bi-Directional Differential Data Strobe
- 8 bit pre-fetch
- Burst Length (BL) switch on-the-fly BL8 or BC4(Burst Chop)
- Supports ECC error correction and detection
- On-Die Termination (ODT)
- Temperature sensor with integrated SPD
- This product is in compliance with the RoHS directive.
- Per DRAM Addressability is supported
- Internal Vref DQ level generation is available
- Write CRC is supported at all speed grades
- CA parity (Command/Address Parity) mode is supported
- RoHS Compliant and Halogen-Free

SPECIFICATIONS

CL(IDD)	21 cycles
Row Cycle Time (tRCmin)	45.75ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	350ns(min.)
Row Active Time (tRASmin)	32ns(min.)
Maximum Operating Power	*
UL Rating	94 V - 0
Operating Temperature	0° C to +85° C
Storage Temperature	-55° C to +100° C

*See IDD Specifications (page 2)

Module Assembly

DRAM: HYNIX (C-DIE)




Continued >>

IDD Specifications

IDD		unit
Symbol	2933	
IDD0	600	mA
IDD0A	600	mA
IDD1	663	mA
IDD1A	693	mA
IDD2N	511	mA
IDD2NA	511	mA
IDD2NT	578	mA
IDD2NL	356	mA
IDD2NG	510	mA
IDD2ND	466	mA
IDD2NP	522	mA
IDD2P	348	mA
IDD2Q	473	mA
IDD3N	950	mA
IDD3NA	949	mA
IDD3P	808	mA
IDD4R	1331	mA
IDD4RA	1346	mA
IDD4RB	1340	mA
IDD4W	1289	mA
IDD4WA	1325	mA
IDD4WB	1224	mA
IDD4WC	1281	mA
IDD4WP	1447	mA
IDD5B	4995	mA
IDD5F2	3498	mA
IDD5F4	2867	mA
IDD6N	679	mA
IDD6E	1083	mA
IDD6R	290	mA
IDD6A	1151	mA
IDD7	1542	mA
IDD8	179	mA

IPP		unit
Symbol	2933	
IPP0	29	mA
IPP1	33	mA
IPP2N	16	mA
IPP2P	16	mA
IPP3N	19	mA
IPP3P	19	mA
IPP4R	53	mA
IPP4W	53	mA
IPP5B	491	mA
IPP5F2	323	mA
IPP5F4	269	mA
IPP6N	65	mA
IPP6E	115	mA
IPP6R	28	mA
IPP6A	101	mA
IPP7	139	mA
IPP8	16	mA

MODULE DIMENSIONS



The product images shown are for illustration purposes only and may not be an exact representation of the product. Kingston reserves the right to change any information at anytime without notice.