



kingston.com/ssd

DATA CENTER DC1000M U.2 NVME SSD

Enterprise Class U.2 NVMe SSD with PLP

Data Center DC1000M

The Kingston DC1000M U.2 NVMe SSD features high-storage capacity and best-in-class enterprise performance. It offers a high-performance Gen 3.0 x4 PCIe NVMe interface enabling high throughput and low latency on standardized platforms. It's designed to deliver up to 540K IOPS of random read performance and 3GB/s of throughput. The DC1000M is backed by strict QoS requirements to ensure predictable random IO performance as well as predictable latencies over a wide range of workloads.

The U.2 form factor design (2.5", 15mm) works seamlessly with the latest generation servers and storage arrays utilizing PCIe and U.2 backplanes. It's hot pluggable which makes the challenges of serviceable PCIe storage an issue of the past.

It also features enterprise-class features such as end-to-end data path protection, power loss protection (PLP), and telemetry monitoring for increased data center reliability. Backed by Kingston's legendary pre- and post-sales support and a five-year limited warranty. Capacities¹ range from 960GB to 7.6TB.

Applications

The "mixed-use" workload drive makes it ideal for running a wide range of customer applications including:

- Virtualization
- High performance cloud service
- Web hosting caching
- High-resolution media capture and transport
- ERP, CRM, GL, OLAP, OLTP, ERM, BI, and EDW workloads

- › Enterprise-class U.2 NVMe PCIe SSD Gen 3.0 x4 SSD
- › High performance over 3GB/s
- › Predictable low latency and high I/O consistency
- › On-board power loss protection (PLP)

[more >>](#)

FEATURES / BENEFITS

Data Center NVMe Performance — Incredible I/O consistency with speeds of up to 3GB/s and 540K IOPS.

Enterprise-Class Mixed-Use Storage — An exceptional balance of consistent I/O delivery with high read and write IOPS performance to manage a wide range of transactional workloads.

Reduce Application Latencies — Quality of Service (QoS) delivers ultra-low transactional latency for large data sets and various web-based applications.

On-board Power Loss Protection (PLP) — Enterprise-class protection to reduce possibility of data loss or corruption on ungraceful powerfails.

SPECIFICATIONS

Form factor

U.2, 2.5" x 15mm

Interface

PCIe NVMe Gen3 x4

Capacities¹

960GB, 1.92TB, 3.84TB, 7.68TB

NAND

3D TLC

Sequential read/write

960GB – 3,100MBs/1330MBs 1.92TB – 3,100MBs/2600MBs
3.84TB – 3,100MBs/2700MBs 7.68TB – 3,100MBs/2800MBs

Steady-state 4k read/write

960GB – 400,000/125,000 IOPS 1.92TB – 540,000/205,000 IOPS
3.84TB – 525,000/210,000 IOPS 7.68TB – 485,000/210,000 IOPS

Latency^{2, 3, 4}

TYP read/write: <300 μ s / <1 ms

Static and dynamic wear leveling

Yes

Power loss protection (power caps)

Yes

Enterprise SMART tools

reliability tracking, usage statistics, SSD life remaining, wear leveling, temperature

Endurance

960GB — 1681 TBW (1 DWPD/5yrs)^{5,6} (1.6 DWPD/3yrs)^{5,6}
1.92TB — 3362 TBW (1 DWPD/5yrs)^{5,6} (1.6 DWPD/3yrs)^{5,6}
3.84TB — 6725 TBW (1 DWPD/5yrs)^{5,6} (1.6 DWPD/3yrs)^{5,6}
7.68TB — 13450 TBW (1 DWPD/5yrs)^{5,6} (1.6 DWPD/3yrs)^{5,6}

Power consumption

960GB: idle: 5.14W	average read: 5.25W	average write: 9.10W
max read: 5.64W	max write: 9.80W	
1.92TB: idle: 5.22W	average read: 5.31W	average write: 13.1W
max read: 5.70W	max write: 13.92W	
3.84TB: idle: 5.54W	average read: 5.31W	average write: 14.69W
max read: 6.10W	max write: 15.5W	
7.68TB: idle: 5.74W	average read: 5.99W	average write: 17.06W
max read: 6.63W	max write: 17.88W	

Storage temperature

-40°C ~ 85°C

Operating temperature

0°C ~ 70°C

Dimensions

100.09mm x 69.84mm x 14.75mm

Weight

160(g)

Vibration operating

2.17G Peak (7–800Hz)

Vibration non-operating

20G Peak (10–2000Hz)

MTBF

2 million hours

Warranty/support⁶

limited 5-year warranty with free technical support



KINGSTON PART NUMBERS

DC1000M
SEDC1000M/960G
SEDC1000M/1920G
SEDC1000M/3840G
SEDC1000M/7680G

- Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products. For more information, go to Kingston's Flash Guide at kingston.com/flashguide.
- Workload based on FIO, Random 4KB QD=1 workload, measured as the time taken for 99.9 percentile of commands to finish the round-trip from host to drive and to host.
- Measurement taken once the workload has reached steady state but including all background activities required for normal operation and data reliability.
- Based on 960GB capacity.
- Drives Writes Per Day (DWPD) derived from the JEDEC Enterprise Workload (JESD219A).
- Limited warranty based on 5 years or when the usage of an NVMe SSD as indicated by Kingston's implementation of the Health attribute "Percentage Used" reaches or exceeds a normalized value of one hundred (100) as indicated by the Kingston SSD Manager (kingston.com/SSDManager). For NVMe SSDs, a new unused product will show a Percentage Used value of 0, whereas a product that reaches its warranty limit will show a Percentage Used value of greater than or equal to one hundred (100).

